

Product Datasheet

CU-M001-SB / CU-M001-21-SB / SD21-SB / SL1200-SB / ESN100-SB / ESN200-SB

PanelPC 9inch touch display

Specifications

Description	Multi - PanelPC 9inch touch display 9" Touch display. Resistive touch, Resolution 800 x 480. LED backlight. 320 Nits. Viewing angle 80/80/80/80 degrees 65565 Colours Night dimming via touch or NMEA
Input/Output	1 LAN. IEC 61162-450 3 NMEA in. 2 NMEA out. NMEA 0183, IEC61162-1/2 Internal alarm beeper.
included in	CU-M001-SB: DL2 Doppler speed log. CU-M001-21-SB: DL21 Doppler speed log. SD21-SB: SD21 Satlog. SL1200-SB: SL1200 Satlog. ESN100-SB: ESN100 Echo sounder. ESN200-SB: ESN200 Echo sounder.
Package consist of	9" Control unit. Connector female
Mounting options	Flush mount. (Purchase option wall mount/desktop mounting bracket Part number MB-0002)
Packaging dimensions	325 x 125 x 230 mm
Packaging weight	1,2 kg
Power consumption	24 V DC (+/-10%). Max 10 W, typical 6 W.
IP rating	Flushmount front: IP 22, back:IP 20
Operating temperature	-15 to 55°C
Storage temperature	-20 to 70°C
Humidity	10 to 90% relative. No condensation

