

# SKIPPER

## Multi Repeater

CD401MR-SB

### Operation and Installation Manual



SKIPPER Electronics AS  
Enebakkveien 150  
P. O. Box 151, Manglerud  
0612 Oslo, Norway  
[www.skipper.no](http://www.skipper.no)

Telephone: +47 23 30 22 70  
Telefax: +47 23 30 22 71  
E-mail: [support@skipper.no](mailto:support@skipper.no)  
Co. reg. no: NO-965378847-MVA

Document no: DM-G003-SB  
Edition: 20100702



CD401MR-SB  
Operation and Installation Manual  
July 2010  
Version 1.10 20100702

Weitergabe sowie vervielfältigung dieser unterlage, verwertung und mitteilung ihres inhaltes nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu schadenersatz.

Toute communication ou reproduction de ce document, toute exploitation ou communication de ou son contenu sont interdites, sauf autorisation expresse. Tout manquement à cette règle est illicite et expose son auteur au versement de dommages et intérêts.

Copying of this document, and giving it to others and the use or communication of contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages.

Sin nuestra expresa autorización, queda terminantemente prohibida la reproducción total o parcial de este documento, así como su uso indebido y/o su exhibición o comunicación a terceros. De los infractores se exigirá el correspondiente resarcimiento de daños y perjuicios.

# TABLE OF CONTENTS

<b>Overview.</b>	5
<b>Terminology.</b> Terms used in this manual	6
<b>Units</b>	6
<b>Abbreviations</b>	6
<b>Introduction.</b> The Multi Repeater	7
<b>Chapter 1.</b> Physical installation	8
<b>The Dimming Inputs</b>	9
<b>Chapter 2.</b> Setting up and using the Compact Display	10
<b>Principles</b>	10
<b>Runtime screens</b>	10
<b>Menu screens</b>	10
<b>Shifting screens</b>	10
<b>Activating the runtime screens</b>	11
<b>Menu Diagram</b>	12
<b>Setup of inputs</b>	14
<b>Changing of the baud rate</b>	14
<b>Demo mode</b>	14
<b>Master Reset (Factory Default Settings)</b>	14
<b>Chapter 3.</b> Configuring the screens	15
<b>Run screens</b>	15
<b>Accepted NMEA sentences</b>	15
<b>Configuration and operational screen</b>	16
<b>Configuring of screens</b>	16
Depth:	17
Speed:	18
Distance:	19
Heading:	20
Rotation:	21
Pitch and Roll:	22
Wind:	23
Temperature:	25
Drive:	26
Clock/UTC:	27
Display Dimming Control:	27
Auxillary:	28
<b>Error Handling</b>	29

---

<b>Chapter 4. Maintenance</b>	<b>30</b>
<b>Routine maintenance</b>	<b>30</b>
<b>Checking your version</b>	<b>30</b>
<b>Firmware upgrade</b>	<b>30</b>
<b>Mounting the Multi Repeater facing aft</b>	<b>30</b>
<b>Appendix 1. Specifications and mechanical drawing</b>	<b>31</b>
<b>System specification</b>	<b>31</b>
<b>Display</b>	<b>31</b>
<b>inputs/outputs</b>	<b>31</b>
<b>Mechanical dimensions</b>	<b>32</b>
<b>Appendix 2. ACCEPTED NMEA 0183 SENTENCES</b>	<b>33</b>
<b>Summary</b>	<b>33</b>
<b>Detailed description</b>	<b>35</b>
<b>Appendix 3. Sending the system for repair</b>	<b>43</b>
<b>Appendix 4. Other options with the Multi Repeater</b>	<b>44</b>
<b>Compact options</b>	<b>44</b>
<b>Changing the system/adding options</b>	<b>45</b>
<b>Notes:</b>	<b>46</b>

# OVERVIEW.

---

## Terminology

Terms, units and abbreviations used in this manual.

## Introduction

This part introduces you to the elements of the Multi Repeater (MR) system.

## Chapter 1 – Physical installation

Correct installation of the system will ensure problem free service for many years. This section explains the main steps to get your system working.

## Chapter 2 – Setting up and using the Compact Display

The Compact display is a flexible intuitive display allowing data to be displayed in a user friendly way. It is also a primary system and can be integrated into the navigation system as regulation stipulate. This chapter explains how to set up the unit.

## Chapter 3 – Operation

Once the system is installed and operational, the user can change the screen to show the data of interest at any time. This section explains the operation of the system.

## Chapter 4 – Maintenance

It is a good idea to verify your systems performance from time to time. This chapter describes how to check interfaces and other issues. In the event of malfunction, this is a good place to start for trouble shooting.

## Appendix 1 – Specifications and drawings

Here you will find more details of how the system works and which factors are important to know when using it.

## Appendix 2 – Accepted NMEA sentences

This section describes the inputs accepted by the compact display in this configuration

## Appendix 3 - Sending the system for repair

In the unfortunate case of a failure that requires a factory repair, the described return sequence should be followed.

## Appendix 4 - Other options with the Multi Repeater

The Compact can be used in a number of different system both as a repeater and a speed log. This section explains what is available and how to activate the options.

## TERMINOLOGY. Terms used in this manual

### UNITS

Unless otherwise stated, all values shown on the display are as follows:

Depth	Meters
Speed	Nautical Miles per hour (knots)
Distance	Nautical Miles (nm)
Heading	Degrees (0 – 359.9°)
Rotation	Degrees per minute (°/min)
Pitch and Roll	Degrees (0 – 359.9°)
Wind	Nautical Miles per hour (knots)
	Meter per seconds (m/s)
	Beaufort (Bft)
Temperature	Degrees Celcius (°C)
Speed Revolutions	Revolutions per minute (rev/min)
Rudder Angle	Degrees (0 – 359.9°)
Propeller Pitch	Percentage of maximum (0 -100 %)
Clock /UTC	hh:mm (00:00 – 23:59)


### ABBREVIATIONS

In addition the following symbols are used on the Runtime screens:

T <sub>p</sub>	Daily trip (in nm)
T <sub>L</sub>	Total measured distance travelled (in nm)
°	Degrees
%	Percentage
←↑→↓	Direction

## INTRODUCTION. The Multi Repeater


The SKIPPER Multi Repeater allow important values from a variety of systems to be displayed anywhere on the vessel. The Compact is unique in its simple and flexible way to display vital data in almost all conditions, from no light to bright sunlight. In addition, it is classed to IP 56 allowing it to be mounted outside and used in any conditions. The unit is a standard 144 mm format allowing it to be mounted in tight spaces or overhead.



## CHAPTER 1. Physical installation

The Multi Repeater CD401MR is a stand alone unit and does not require additional circuitry. It should be supplied by a 24 V (19 V-36 V) 25 W DC supply and the cabling of the system is as per diagram below. The unit is supplied with 2 m of cable (12 core). This can be extended without problem. Only the wires in use need extending.


**Note:** Mounting drawing is available in Appendix 1.





# THE DIMMING INPUTS

Pulses of at least 60 ms on the dimming up and dimming down cables will cause the dimming to change by one level. The inputs are optocoupled and therefore require an external voltage to operate, (5 Volt -24 Volt (Typically 5/12/24 Volt)).



## CHAPTER 2. Setting up and using the Compact Display

### PRINCIPLES

The Compact Display is a flexible dot matrix LED display designed to display navigation data. The Multi repeater can be user programmed to show most kinds of numerical data from NMEA messages. It can also be used as a primary sensor display for speed logs showing the speed values produced by the sensor. The Compact with its JB60CD box meets all the requirements of a primary device both functionally and electrically. On its own it meets the requirements as a repeater. The Compact has three user definable alphanumeric displays, each allowing up to 4 lines to be displayed. When the device is used as a primary device, some of these screens will be fixed.

### RUNTIME SCREENS

The Compact Display starts up in runtime mode. By pressing the MENU button, the preset runtime screens can be selected. The unit can be dimmed in any of the runtime screens using the UP and DOWN buttons.

### MENU SCREENS

To change the setup of the Multi Repeater, the user must simultaneously press MENU and SET buttons. This will give access to a menu system allowing the user to scroll up and down the sub menus and functions using UP, DOWN and SET buttons to select. To move back up a menu, the MENU button must be pressed. The middle underlined line is the selected line. The other lines are dimmed.



The menu structure is shown in the MENU DIAGRAM. The menus are product dependant, only the relevant menus are accessible. Some menus are available in all setups.


Press both MENU and SET buttons to activate the menus. Press and hold MENU to return to runtime screen

### SHIFTING SCREENS

The system can be made to shift, with a five second period, between the activated screens. Pressing MENU will pause this function, and holding MENU will reactivate it.


## ACTIVATING THE RUNTIME SCREENS

The system has three user preset runtime screens (SCR1, SCR2, SCR3). The Screen Menu allows the user to configure and choose which runtime screens to be included in normal operation. UP and DOWN buttons will scroll to the available screens. By using the SET button, the user can control each individual screen to ON, OFF or SHIFTING. Screens set to ON are available to be displayed by pressing the MENU button. Screens set to OFF will not be displayed. Screens set to SHIFTING will be shown on the display periodically. Each shifting runtime screen will be displayed for 5 seconds.



If any screens are configured to SHIFTING, these selected screens will automatically start displaying periodically. The shifting of these preset runtime screens are stopped if the MENU button is pressed in runtime mode. By holding down the MENU button longer, the shifting will be started again.

# MENU DIAGRAM



**Menus, scrollable menu system**  
 Accessed with SET and MENU pressed simultaneously  
 ▲ Next sub menu  
 ▼ Prev sub menu  
 SET select sub menu  
 MENU return

**System Setup (SETUP)**  
 Setup the system parameters  
 ▲ Next sub menu  
 ▼ Prev sub menu  
 SET select sub menu  
 MENU return

**Baud Settings (NMEA)**  
 ▲ Higher value  
 ▼ Lower value

**Diagnostics Advanced Setup (DIAG)**  
 Diagnose and adjust less used parameters  
 ▲ Next sub menu  
 ▼ Prev sub menu  
 SET select sub menu  
 MENU return

**Code option activation (CODE)**  
 Shows serial no  
 Code number with active digit underlined  
 ▲ Increment underlined digit  
 ▼ Move to next digit  
 SET activates the displayed code

**Upgrade mode (UPGRD)**  
 Allow the system to upgrade from cable

**Demo (DEMO)**  
 ▲ Increment mode  
 ▼ Decrement mode  
 MENU accept mode  
 Mode 1 = dynamic  
 Mode 2 = static  
 Off

**Splash screen (INFO)**  
 ▲ Dimming up  
 ▼ Dimming down  
 Option info  
 Software version

**Self Tests (TEST)**  
 ▲ Next test  
 ▼ Previous test  
 SET starts selected test

## SETUP OF INPUTS

The system will allow many NMEA formats to be displayed. The system will automatically update recognized formats.

## CHANGING OF THE BAUD RATE

The NMEA (IEC61162-1) standard is 4800 baud. Some vessels run with higher baud rates. 4800, 9600, 19200, 38400, 57600 and 115200 baud rates can be selected in the baud screen of the setup menu.

## DEMO MODE

A demo mode is available, and can be activated with MENU button in the diagnostics menu. Two modes are available.

- **Mode 1** is a dynamic demo mode taking the present value as the start point and slowly varying all the available values.
- **Mode 2** is a static mode taking the present values and keeping them active.

When the demo mode is active, alarms will be disabled, and the screen will indicate the demo state with a blinking S in the upper right corner. The user can turn off the demo mode from the demo screen, or by recycling the power. The demo mode will turn off automatically after 10 hours.

## MASTER RESET (FACTORY DEFAULT SETTINGS)

The factory default settings can be restored by performing the following operations:

1. Select CODE in diagnostic (DIAG) menu.
2. Press the SET button (**Note:** Do not change code value).

The unit will now restart with factory default settings.



## CHAPTER 3. Configuring the screens

### RUNTIME SCREENS

The unit starts up in runtime mode. By pressing the MENU button, the preset runtime screens (SCR1, SCR2, SCR3) can be selected. The unit can be dimmed in any of the runtime screens using the UP and DOWN buttons. If Trip/Total are selected as a displayed parameter, they can be toggled using the SET button. If wind speed is selected as a displayed parameter, the unit can be toggled between knots, m/s, or Beaufort using the SET button.



### ACCEPTED NMEA SENTENCES

When using the Compact Display as a Multi Repeater, the display could be user programmed to show the most commonly used NMEA 0183 (IEC61162) messages for:

Depth	Below surface, keel and transducer
Speed	Over ground and through water (longitudinal, transverse, aft and relative)
Distance	Total/trip for both ground and water
Heading	True, magnetic and relative
Rotation	Rate of turn and direction
Pitch and roll	In degrees
Wind	Speed and direction (true, magnetic and relative)
Temperature	Water and air
Drive	RPM (Revolutions Per Minute), propeller pitch and rudder position
Clock	UTC (Universal Time Coordinated), local time and Expected Time of Arrival (ETA)
Dimming	Display dimming
Auxillary	User defined NMEA messages

A summary of supported NMEA sentences is listed in Appendix 2.

## CONFIGURATION AND OPERATIONAL SCREEN

The programming of parameters to show on the screen is very flexible. It is advise to add leading text before the parameters and not mixing to many different messages. A typical configuration is to show two related parameters on the screen simultaneously with leading text. Arrows are added to some parameters for better readability. Press MENU and SET button simultaneously to enter the main menu screen, select CONFG and then select wanted screen (CFG1, CFG2 or CFG3) to start configure wanted screen. See chapter 2 "Setting up and using the Compact Display" on how to program the display to show wanted information on the screen.

## CONFIGURING OF SCREENS

The 3 user programmable screens can be set up using the Config (CONFG) menu. This submenu allows the user to select one of the three screens, and on entering the Config screen, the user can change the data type to be displayed in each of the 4 screen positions. UP and DOWN will change the data type, SET will move to the next screen position.



Placing TXT in the bottom 4<sup>th</sup> line or 3<sup>rd</sup> and 4<sup>th</sup> line will cause the data to spread out showing fewer data points. The system will not allow you to mix speed data from different sources on the same screen. Having 2 TXT lines after each other will also rearrange the positioning. (See examples on next page).

The non-active parameters will continue showing the dimmed present data, when not selected. Some combinations of data are not allowed, as they may cause confusion. These will be automatically corrected. Note that the leading text is identical for some data, and information about talkers are ignored. Regulations require the user to be able to identify which data they are looking at. This can be achieved by using the TXT function or a sticker on the unit.



## Depth

The NMEA sentences DPT, DBS, DBT, DBK and PSKPDPT are all supported for receiving information about the depth. The use of the DPT sentence is recommended when available. Depth values in feet and fathoms (from DBK, DBT and DBS) are converted to meters. The screen will display either DEPTH-S (depth below surface), DEPTH-T (depth below Transducer) or DEPTH-K (depth below keel) depending of the received sentences (DBS, DBT or DBK) or the offset value in DPT. The proprietary sentence PSKPDPT will also indicate the transducer location with an arrow in the text line.

The depth is always displayed in meters. Depth values below 10 meters are displayed with 2 decimals, depth values between 10 and 100 meters are displayed with 1 decimal and depth above 100 meters are displayed without decimals.

Maximum depth value to be displayed is 9999 meters.

**Config.  
screen:**



**Runtime  
screen:**



## Speed

The NMEA sentence VBW is supported for receiving information about the speed through water and speed over ground (bottom) for longitudinal, tranverse and transverse aft. The NMEA sentences VHW and VTG are supported for receiving information about relative speed.

- An arrow, indicating the direction, is added in front of the value for speed values from the NMEA sentences VBW.
- The relative **speed through water** is fetched from the NMEA sentence VHW.
- The relative **speed over ground** is fetched from the NMEA sentence VTG.
- Speed value in km/h is converted to knots if speed value in knots is not available.
- Relative speed is displayed without arrows.
- All speed values are displayed in knots with one decimal. Maximum speed value to be displayed is +/- 99.9 knots.

Config.  
screen:



Runtime  
screen:



## Distance

The NMEA sentence VLW are supported for receiving information about distances. The Trip/Total parameters for either water distance or ground distance can be toggled using the SET button.

The distance values are always displayed in nautical miles and the value will wrap around after reaching the maximum value of 99999. Total/trip values below 10 are displayed with two decimals, values between 10 and 1000 with one decimal and values above 1000 are displayed with no decimals.

### Configuration screen:



### Runtime screen:



## Heading

The NMEA sentences VHW, VTG, THS, HDT, HDM and HDG are all supported for receiving information about the heading. It is recommended to use THS instead of HDT and HDG instead of HDM when available. The deviation and variation parameters in HDT are ignored.

If the same heading parameter is received from different talkers, the heading parameter will be prioritized as shown below:

1. Gyro, north seeking (HE).
2. GPS (GP).
3. Compass, magnetic (HC).
4. Others.

An arrow is added on the text line to indicate which direction the bow turns. If no change in heading from previous value, no arrow is displayed.

The heading value is always displayed with one decimal. Legal range for the heading to be displayed, are values in the range from 0 to 359.9 °.

**Config.  
screen:**



**Runtime  
screen:**



Direction of turn is to port.



Direction of turn is to starboard.



No change in heading since last message.

## Rotation

The NMEA sentence ROT is supported for receiving information about the rotation. A steady arrow is added on the text line to indicate which direction the bow turns.

- A positive received value indicates that bow turns to starboard and an arrow to the right is displayed.
- A negative received value indicates that bow turns to port and an arrow to the left is displayed.
- A value of zero indicates no rotation and no arrow is displayed.

Values below 99.9 are displayed with one decimal. Values above 100 are displayed with no decimals. Maximum value to display is +/- 999<sup>o</sup>/min.

### Configuration screen:



### Runtime screen:



## Pitch and Roll

The NMEA sentence XDR, version B is supported for receiving information about the Pitch and Roll.

- A positive received value for Pitch indicates that the bow is up and negative if bow is down.
- A positive received value for Roll indicates that port is up and starboard is down, a negative value indicates that starboard is up and port is down.

Values below 10 degrees are displayed with two decimals and values above 10 degrees with one decimal. Maximum value to be displayed is +/- 359.9°.

### Configuration screen:



### Runtime screen:



## Wind

The NMEA sentences MWV, VWR, VWT and MWD are all supported for receiving information about the wind speed and direction. MWV is recommended instead of VWR and VWT, when available. All wind speed units are accepted (knots (N), m/s (M) and km/h (K)) and converted to wanted speed units to display on the screen. Speed units on the display may be toggled between kn (knots), m/s and Bft (Beaufort) by pressing the SET-button.

A graphical representation of the wind angle is displayed if the following parameters are selected:

- TXT must be selected for the first two parameters.
- One wind angle must be selected.
- Corresponding wind speed from the same NMEA sentence could be selected. Otherwise TXT must be selected.
- The wind angle is represented by an arrow on the screen.

See chapter 2 "Setting up and using the Compact Display" for details how to set up the screen.

The range of values to be displayed, are:

- Speed: 0 - 99.9 knots.
- Heading: 0 – 359.9°.

# Wind, (continued from previous page):

**Config.  
screen:**



**Runtime  
screen:**



SET button has been pressed for toggling the speed units to m/s.

**Configuration  
screen:**



Graphical representation

**Runtime  
screen:**



SET button has been pressed for changing between knots, m/s and Beaufort units.



## Temperature

The NMEA sentences MTA, MTW and MDA are supported for receiving information about the air (MTA or MDA) and water (MTW) temperatures. Air temperature from MDA is used if data from MTA is not available.

Temperatures are displayed in degree Celcius. Values below 10 degrees are displayed with two decimals and values above 10 degrees with one decimal. The maximum/minimum temperatures to be displayed are +/- 99.9 °C.

### Configuration screen:



### Runtime screen:



## Drive

- The NMEA sentence RPM is supported for receiving information about the speed revolutions (rev/min) and propeller pitch (% of maximum).
- The NMEA sentence RSA is supported for receiving information about the rudder angle.


The speed revolution values below 999.9 is displayed with one decimal and values above 1000 is displayed without decimals. Propeller pitch values below 10 degrees are displayed with two decimals and values above 10 degrees with one decimal.

- Max./min. value to be displayed for speed revolution is +/- 9999 rev/min.
- Max./min. value to be displayed for propeller pitch is +/- 100 %.
- Max./min. value to be displayed for rudder angle is +/- 359.9 °.

### Configuration screen:



### Runtime screen:



## Clock/UTC

The UTC is fetched from either of the NMEA sentences ZTG, ZDA, GGA or RMC, prioritized in the same order. The NMEA sentences ZDA is used for receiving information about the local time. The NMEA sentences ZTG is used for receiving information about expected time of arrival. Maximum offset for displayed time of "Expected Time of Arrival" is 24 hours. All time values are displayed with the format hh:mm, where hh are hours and mm are minutes.

**Config.  
screen:**



**Runtime  
screen:**



Local time is  
UTC – (1h 30 min).

Expected Time of  
Arrival is UTC +  
(20h 45 min).

## Display Dimming Control

The brightness of the display can be controlled by the NMEA sentence DDC. Note that the brightness also can be controlled by buttons on the display and remote dimmer control (IR30DIM). Both the Brightness Percentage and Display Dimming Preset are supported in the NMEA sentence DDC. (See Appendix 2).

## Auxillary

A proprietary NMEA sentence is supported which allow the user to define up to 4 additional parameters to be displayed from any specified NMEA sentence(s). This proprietary NMEA sentence has the following format:

`$PSKPPCCPNMEA, <Auxillary number>, <Header>, <Data Field number.>, <Type>, < Status field number >, < Status valid character >, <Text>*hh<CR><LF>`

**Example:** Fetch a proprietary NMEA sentence for roll & pitch and display the values: `$PPPRP, <a>, <b><CR><LF>` where <a> is roll data parameter and <b> is pitch data parameter.

Fetch also the parameters for both port and starboard rudder angle from the following NMEA message: `$SGRSA, <a>, A, <b>, A<CR><LF>` where <a> is starboard rudder sensor and <b> is port rudder sensor and 'A' is status for each corresponding data field parameter. The following NMEA sentences must be sendt to the Compact display to accept these parameters:

`$PSKPPCCPNMEA, 1, PPRP, 0, 8,, ROLL<CR><LF>`  
`$PSKPPCCPNMEA, 2, PPRP, 1, 8,, PITCH<CR><LF>`  
`$PSKPPCCPNMEA, 3, SGRSA, 0, 8, 1, A, SRUD<CR><LF>`  
`$PSKPPCCPNMEA, 4, SGRSA, 2, 8, 3, A, PRUD<CR><LF>`

Select the AUX1 in the meny to display the roll parameter, select the AUX2 in the meny to display the pitch parameter, select AUX3 in the menu to display the starboard rudder angle and AUX4 in the menu to display the port rudder angle.

### Configuration screen:



### Runtime screen:



### Received NMEA sentence:

`$PPPRP, 12.31, 1.22`

`$SGRSA, 3.4, A, 0.2, A`

## ERROR HANDLING

All parameters within each NMEA sentences are checked for checksum, legal range, validity and timeout.

### Bad checksum ( - - - - )

If the Checksum Field (\*hh) is present, the value is checked. The screen will indicate bad checksum by displaying minus signs instead of the value (- - - -). If no Checksum Field is present, no checking is performed.

### Illegal range and validity ( . . . . )

Some values must be within a range. If a value is out of range, the following exception is performed:

- **Wrap around:** The displayed value will start from zero again after reaching the maximum/minimum value (Trip values, only).
- **Limited value:** The maximum or minimum value will be displayed (Speed and temperature values).
- **Illegal value:** The value has no meaning (ex. heading values above 360°). The screen will indicate illegal value by displaying dots instead of the value (. . . .).

A Null field is a field in the NMEA sentence without any character between two delimiter characters. A Null field indicates that the value is unreliable or not available. The screen will indicate a Null field by displaying dots instead of the value (. . . .) if no value is received within the timeout timeframe.

Some parameters has a status parameters associated with them (A = data valid, V = data invalid). The screen will indicate an invalid parameter by displaying dots instead of the value (. . . .) if no new valid value is received within the timeout timeframe.

### Timeout (ERROR)

The timeout value for each parameter within each NMEA sentence is 10 seconds. The screen will indicate timeout by displaying an error message (ERROR) if no new value is received within the timeout timeframe.

## CHAPTER 4. Maintenance

### ROUTINE MAINTENANCE

No maintenance is required. The screen can be cleaned with a soft cloth.

### CHECKING YOUR VERSION

If the Info screen is activated on the run screens, the system type and firmware version can be read from there. Otherwise the same screen can be obtained in the diagnostics menu. The system type will be one of the following:

CD E1	Compact display EML 1 Axis.
CD E2	Compact display EML 2 Axis.
CD EB	Compact display EML 2 Axis backwards.
CD LR	Compact display Log Repeater.
CD MR	Compact display Multi Repeater.
CD MB	Compact display Multi Repeater backwards.

The system will be locked to one of these setups, but can be changed to one of the other systems (with an additional cost) using a code (see Appendix 4).

### FIRMWARE UPGRADE

The system is undergoing continuously improvements, and periodically new firmware will be released. A chip can be supplied (with an additional cost) with the new software. This is changed by removing the backplate of the Compact display.

### MOUNTING THE MULTI REPEATER FACING AFT.

The Compact Display could also be set up to operate in "Multi Repeater, Backwards" mode. In this mode all speeds are in opposite direction. See the section "MAINTENANCE" on how to change the system setup. The parameters in "Multi Repeater, Backwards" mode will be replaced according to the following:

STWWL = - STWWL	SOGBL = - SOGBL
STWWT = - STWWA	SOGBT = - SOGBA
STWWA = - STWWT	SOGBA = - SOGBT

# APPENDIX 1. Specifications and mechanical drawing

## SYSTEM SPECIFICATION

Power Supply	DC: 19 - 36 V/25 Watt.
Display	28 x 30 pixel, Alphanumeric LED (red). With dimming.
Languages	English.
Accessories	Dimming control.
Classification	IMO MED B.
Service	Available in most major harbours, world-wide through extensive dealer network. See <a href="http://www.skipper.no">www.skipper.no</a> for further information.


## DISPLAY

Weight (display)	1.3 kg.
Cable length	2 m (can be extended).
Compass safe distance (min)	30 cm.
User adjustable screens	3
Parameters per screen	2 with text, 3 with single text line.

## INPUTS/OUTPUTS

Outputs	2 x NMEA (IEC61162-1) (2007).
Inputs	1 x NMEA (IEC61162-1) (2007).
	External Dimming (up and down pulses).

# MECHANICAL DIMENTIONS





## APPENDIX 2. ACCEPTED NMEA 0183 SENTENCES SUMMARY

	NMEA Sentence	Description	Parameter Name	Screen name
<b>Depth</b>	DPT	Water Depth in meters	DPT	DEPTH-K DEPTH-T DEPTH-S
	DBK	Water Depth below Keel in meters	DBK	DEPTH-K
	DBT	Water Depth below Transducer in meters	DBT	DEPTH-T
	DBS	Water Depth below Surface in meters	DBS	DEPTH-S
	PSKPDPT	SKIPPER proprietary depth sentence	PDPT	DEPTH-K DEPTH-T DEPTH-S
<b>Speed</b>	VBW	Longitudinal Water Speed	STWWL	STW
		Transverse Water Speed	STWWT	STW
		Transverse Water Speed, Aft	STWWA	STW
		Longitudinal Ground Speed	SOGBL	SOG
		Transverse Ground Speed	SOGBT	SOG
		Transverse Ground Speed, Aft	SOGBA	SOG
	VHW	Speed Through Water in knots, relative	STW-R	STW-R
VTG	Speed over Ground in knots, relative	SOG-R	SOG-R	
<b>Distance</b>	VLW	Water-track Distance since reset	TRIPW	TRIPW
		Water-track Total distance	TOTLW	TOTLW
		Bottom-track Distance since reset	TRIPB	TRIPB
		Bottom-track Total distance	TOTLB	TOTLB
<b>Heading.</b>	VHW	Heading, degrees, true	HDW-T	HDG.T
		Heading, degrees, magnetic	HDW-M	HDG.M
	VTG	Heading (Course Over Ground), degrees, true	COG-T	COG.T
		Heading (Course Over Ground), degrees, magnetic	COG-M	COG.M
	THS	Heading, degrees, true	THS	HDG.T
	HDT	Heading, degrees, true	HDT	HDG.T
	HDM	Heading, degrees, magnetic	HDM	HDG.M
	HDG	Heading, degrees, magnetic	HDG	HDG.M
<b>Rotation</b>	ROT	Rate of Turn in degrees/minute	ROT	ROT


	<b>NMEA Sentence</b>	<b>Description</b>	<b>Parameter Name</b>	<b>Screen name</b>
<b>Pitch and roll</b>	XDR	Pitch	PITCH	PITCH
		Roll	ROLL	ROLL
<b>Wind</b>	MWV	Wind angle, Theoretical (True)	MWVAT	WIND-T
		Wind angle, Relative	MWVAR	WIND-R
		Wind Speed in knots	MWVNT	WIND-T
		Wind speed in m/s	MWVMT	WIND-T
		Wind speed in Beaufort	MWVBT	WIND-T
		Wind Speed in knots	MWVNR	WIND-R
		Wind speed in m/s	MWVMR	WIND-R
		Wind speed in Beaufort	MWVBR	WIND-R
	VWR	Wind angle, Relative	VWR-A	WIND-R
		Wind Speed in knots	VWR-N	WIND-R
	VWT	Wind angle, True	VWT-A	WIND-T
		Wind Speed in knots	VWT-N	WIND-T
	MWD	Wind angle, True	MWD-T	WIND-T
		Wind angle, Magnetic	MWD-M	WIND.M
		Wind Speed in knots	MWD-N	WIND
<b>Temp.</b>	MTA, MDA	Air Temperature in degree Celcius	ATEMP	AIRTEMP
	MTW	Water Temperature in degree Celcius	WTEMP	W.TEMP
<b>Drive</b>	RPM	Revolutions / min	RPM	RPM
		Propeller Pitch (% of maximum)	PPTCH	P.PITCH
	RSA	Rudder Sensor Angle	RSA	RUDDER
<b>Clock/ UTC</b>	ZTG, ZDA, GGA, RMC	UTC (hh:mm)	UTC	UTC
	ZDA	Local Time (hh:mm)	LOC	LOC
	ZTG	Expected Time of Arrival (UTC) (hh:mm)	ETA	ETA
<b>Display dimming</b>	DDC	Display Dimming Control		
<b>Auxillary</b>	Defined by proprietary NMEA sentence	User defined message 1 (Auxillary 1)	AUX1	Defined by proprietary NMEA sentence
		User defined message 2 (Auxillary 2)	AUX2	
		User defined message 3 (Auxillary 3)	AUX3	
		User defined message 4 (Auxillary 4)	AUX4	

## DETAILED DESCRIPTION

### Depth:

#### Depth

\$--DPT, x.x, x.x\*hh<CR><LF>




#### Parameter

name

DPT

#### Depth Below Surface


\$--DBS, x.x, f, x.x, M, x.x, F\*hh<CR><LF>



DBS

#### Depth Below Transducer


\$--DBT, x.x, f, x.x, M, x.x, F\*hh<CR><LF>



DBT

#### Depth Below Keel


\$--DBK, x.x, f, x.x, M, x.x, F\*hh<CR><LF>



DBK

#### SKIPPER Proprietary sentence

\$--PSKPDPT,x.x,x.x, , , ,c-c\*hh<CR><LF>



PDPT


**Note 1:** Positive value indicates distance from transducer to water line.  
Negative value indicates distance from transducer to keel.

**Speed:**

**Parameter name**


**Dual Ground/Water Speed**

\$--VBW,x.x,x.x,A,x.x,x.x,A,x.x,A,x.x,A\*hh<CR><LF>




**Water Speed and Heading**

\$--VHW,,,,,x.x,N,x.x,K\*hh<CR><LF>



**Course Over Ground and Ground Speed**

\$--VTG,,,,,x.x,N,x.x,K\*hh<CR><LF>




**Distance:**

**Parameter name**

**Dual Ground/Water Speed**

\$--VLW,x.x,N,x.x,N,x.x,N,x.x,N\*hh<CR><LF>




**Note:** All distance values must be specified in nautical miles.

**Heading:**

**Parameter name**


**Water Speed and Heading**

\$--VHW, x.x, T, x.x, M, , , \*hh<CR><LF>




**Course Over Ground and Ground Speed**

\$--VTG, x.x, T, x.x, M, , , \*hh<CR><LF>



**True Heading and Status**


\$--THS, x.x, a\*hh<CR><LF>



**Note:** The Mode indicator is ignored


**Heading True**

\$--HDT, x.x, T\*hh<CR><LF>




**Heading Magnetic**

\$--HDM, x.x, M\*hh<CR><LF>



**Heading, Deviation and Variation**

\$--HDG, x.x, , , \*hh<CR><LF>




**Rotation:**

**Parameter name**

**Rate Of Turn**

\$--ROT, x.x, A\*hh<CR><LF>




## Pitch and Roll

Parameter name

### Transducer Measurements

\$--XDR, a, x.x, D, PTCH, a, x.x, D, ROLL\*hh<CR><LF>




## Wind:

Parameter name


### Wind Speed and Angle

\$--MWV, x.x, a, x.x, a, A\*hh<CR><LF>




### Relative Wind Speed and Angle

\$--VWR, x.x, a, x.x, N, x.x, M, x.x, K\*hh<CR><LF>



### True Wind and Speed Angle


\$--VWT, x.x, a, x.x, N, x.x, M, x.x, K\*hh<CR><LF>



**Wind:**

**Wind Direction and Speed**


\$--MWD, x.x, T, x.x, M, x.x, N, x.x, M\*hh<CR><LF>



**Temperature:**


**Air Temperature**

\$--MTA, x.x, C\*hh<CR><LF>




**Meteorological Composite**

\$--MDA, , , , , x.x, C, , , , , , , , , , \*hh<CR><LF>



**Water Temperature**


\$--MTW, x.x, C\*hh<CR><LF>



**Drive:**


**Revolutions**

\$--RPM, , , x.x, x.x, A\*hh<CR><LF>



**Rudder Sensor Angle**

\$--RSA, x.x, A, , hh<CR><LF>



**Clock / UTC**

**Parameter name**

**UTC & Time to Destination Waypoint**

\$--ZTG, hhmmss.ss, hhmmss.ss,\*hh<CR><LF>  
 \_\_\_\_\_ Time-to-go (max 24 h) ETA  
 \_\_\_\_\_ UTC of observation UTC

**Time & Date**

\$--ZDA, hhmmss.ss, , , , x.x, x.x\*hh<CR><LF>  
 \_\_\_\_\_ Local zone minutes, 00 to +59 LOC  
 \_\_\_\_\_ Local zone hours, 00 to +/- 13  
 \_\_\_\_\_ UTC of observation UTC

**Global Positioning System Fix Data**

\$--GGA, hhmmss.ss, , , , , , , , , , \*hh<CR><LF>  
 \_\_\_\_\_ UTC of position UTC

**Recommended Minimum Specific GNSS Data**

\$--RMC, hhmmss.ss, , , , , , , , , , \*hh<CR><LF>  
 \_\_\_\_\_ UTC of position UTC

**Display Dimming:**

**Display Dimming Control**

\$--DDC, a, xx,\*hh<CR><LF>  
 \_\_\_\_\_ Brightness Percentage:  
 00 (min) to 99 (max)  
 \_\_\_\_\_ Display Dimming Preset:  
 D = Day time setting (max)  
 K = Dusk setting  
 N = Nighth time setting  
 O = Backlight off setting (min)



**Auxillary:**

SKIPPER proprietary

\$PSKPPCCPNMEA, <Auxillary number>,<Header>,<Data Field number.>,<Type>,  
< Status field number >,< Status valid character >,<Text>\*hh<CR><LF>

<Auxillary number>	The auxillary number for the wanted user defined parameter. Each additional parameter must be defined with an unique auxillary number. Legal values are 1, 2, 3 or 4.
<Header>	This character string follows the '\$'-sign in the specified NMEA sentence. Up to 15 characters could be defined here.
<Data field number>	Field number for the data to receive within the specified NMEA sentence, starting with 0 after the first field delimiter. Legal values will be limited by the maximum number of characters in a NMEA sentence.
<Type>	Data type of the parameter. The following data types are defined: <ul style="list-style-type: none"> <li data-bbox="395 555 575 580">0: Unsigned value</li> <li data-bbox="395 585 552 611">1: Signed value</li> <li data-bbox="395 616 577 641">2: Depth in meters</li> <li data-bbox="395 646 717 671">3: Speed without arrow and postfix</li> <li data-bbox="395 676 703 702">4: Longitudinal speed with arrow</li> <li data-bbox="395 707 686 732">5: Transverse speed with arrow</li> <li data-bbox="395 737 675 762">6: Speed with knots as postfix</li> <li data-bbox="395 767 941 793">7: Heading with arrow to indicate the direction the bow turns</li> <li data-bbox="395 798 736 823">8: Heading / Direction without arrow</li> <li data-bbox="395 828 516 853">9: Rotation</li> <li data-bbox="395 858 549 884">10: Temperature</li> <li data-bbox="395 888 535 914">11: Percentage</li> </ul> <p data-bbox="378 948 994 973">See table of summary of supported data types for user defined messages</p>
<Status field number.>	Field number for status within the specified NMEA sentence, starting with 0 after the first field delimiter. Legal values will be limited by the maximum number of characters in a NMEA sentence.
<Status valid character>	The valid character for the status field is defined here. The data in the data field will only be valid if the staus field contains this specified character. A Null field indicates that the status field is not used and the recieved parameter data is always valid.
<Text>	Character string to be displayed if text (TXT) is selected. Only large english characters are accepted. The string can be up to 5 characters long, but limited to 3 characters for some types, see the description <Type > for limitations.
	The text is truncated if more characters are defined. A Null field is interpreted as blank text.

Summary of supported Data Types for User defined messages:

Data Type No.	Data Type name	Legal Data Type Range		Screen output				Format / Comments
				Out of range (screen)		Within Range		
		Min.	Max.	Below	Above	Pre-fix	Post-fix	
0	Unsigned value	-9999.99	9999.99	'.....'	'.....'	None	None	Values between 0 and 9.99 are displayed with 2 decimals. Values between 10 and 99.9 are displayed with one decimal.
1	Signed value	- 9999.99	9999.99	'.....'	'.....'	None or' - '	None	Values above 100 are displayed without decimals.
2	Depth in meters	0	9999.99	'.....'	'9999'	None	' m '	
3	Speed without arrow and postfix	- 99.9	99.9	'99.9'	'99.9'	None	None	All speed values in knots with one decimal. Negative values are displayed without minus sign.
4	Longitudinal speed with arrow	- 99.9	99.9	'99.9'	'99.9'	'↑' or '↓'	None	All speed values in knots with one decimal. Negative values indicates astern direction.
5	Transverse speed with arrow	- 99.9	99.9	'99.9'	'99.9'	'→' or '←'	None	All speed values in knots with one decimal. Negative values indicates port direction.
6	Speed with knots as postfix	- 99.9	99.9	'99.9'	'99.9'	None	' kn '	All speed values in knots with one decimal. Negative values are displayed without minus sign.
7	Heading with arrow to indicate the direction the bow turns	0	360	'.....'	'.....'	None	' ° '	All values are displayed with one decimal. An arrow ('←' or '→') is added in the text line to indicate direction the bow turns. The <Text> field must therefore be limited to 3 characters for this type. The direction of turn is calculated based on previous heading value.
8	Heading / Direction without arrow	0	360	'.....'	'.....'	None	' ° '	All values are displayed with one decimal.
9	Rotation	- 999	999	'.....'	'.....'	None	' °/m '	Values below 99.9 are displayed with one decimal. Values above 100 are displayed with no decimals. An arrow ('←' or '→') is added in the text line to indicate which direction the bow turns. The <Text> field must therefore be limited to 3 characters for this type. A negative value indicates port direction.
10	Temperature	- 99.99	99.9	'-99.9'	'99.9'	None or' - '	' ° '	Values between 0 and 9.99 are displayed with 2 decimals. Values between 10 and 99.9 are displayed with one decimal.
11	Percentage	-100	100	'.....'	'.....'	None or' - '	' % '	Values between 0 and 9.99 are displayed with 2 decimals. Values between 10 and 99.9 are displayed with one decimal.

## **APPENDIX 3. Sending the system for repair**

---

In case of failure, it may be necessary to send a part of the system back for repair. Make contact with your local dealer for warranty case (list available on [www.skipper.no](http://www.skipper.no)).

On contact with SKIPPER the case will be given a SKIPPER id number. This number should be quoted on all correspondence, and marked clearly on all parts returned.

For normal service/support, please contact SKIPPER Electronics AS on mail [support@skipper.no](mailto:support@skipper.no) or our local dealer (list available on [www.skipper.no](http://www.skipper.no)).

## APPENDIX 4. Other options with the Multi Repeater

### COMPACT OPTIONS

The Compact Display can be set up for one of the following systems:

LR	Speed Repeater	
E1 (EML124 Compact)	Single Axis EML	With Electronic unit (JB60CD), sensor and cables
E2 (EML224 Compact)	Dual Axis EML	With Electronic unit (JB60CD), sensor and cables
EB (EML224 Compact)	Dual Axis EML Backwards	With Electronic unit (JB60CD), sensor and cables
MR	Multi Repeater	
MB	Multi Repeater Backwards	

- **Speed Repeater:** A simple repeater for speed in 1 and 2 axis and trip. Limited functionality.
- **Single Axis EML:** As above plus primary display for speed logs showing longitudinal speed values produced by the sensor.
- **Dual Axis EML:** As above, but showing both longitudinal and transverse speed values produced by the sensor.
- **Dual Axis EML Backwards:** As above, but can be connected to an external switch for showing the speeds in opposite direction.
- **Multi Repeater:** A comprehensive repeater for many of the most common used NMEA messages. Functions also for user defined messages.
- **Multi Repeater Backwards:** As above, but the speeds are shown in opposite direction.

The software for all these systems is stored in the flash memory and the system configuration can be changed using a security code. This code can be obtained from [www.skipper.no](http://www.skipper.no). By sending an order to SKIPPER together with the systems serial number. (Obtained by opening the code screen in diagnostics). On entering the supplied code number, the system options will be set. Please note that the cabling is different for repeaters and speed logs, so these are not compatible without replacing the back plate.

## CHANGING THE SYSTEM/ADDING OPTIONS

The Compact display unit is being developed as a low cost display alternative to full graphics displays already available. Most extra features are available for the Compact and these can be activated using the CODE page in the DIAG menu. On this menu, the systems unique ID is displayed, and the new options can be purchased from the SKIPPER retailer to add extra functions. You will receive a code to be entered into the CODE page by using the arrow buttons.

**NOTE:** It is important to note that pay option codes are unique for each individual unit and will not work on other units.



DIAG menu



CODE page

## NOTES:

-----  
-----  
-----  
-----  
-----  
-----  
-----  
-----  
-----  
-----  
-----  
-----  
-----  
-----  
-----  
-----  
-----  
-----  
-----  
-----  
-----



# SKIPPER

**SKIPPER** Electronics AS  
Enebakkveien 150  
P. O. Box 151, Manglerud  
0612 Oslo, Norway  
[www.skipper.no](http://www.skipper.no)

Telephone: +47 23 30 22 70  
Telefax: +47 23 30 22 71  
E-mail: [support@skipper.no](mailto:support@skipper.no)  
Co. reg. no: NO-965378847-MVA