

Ensure safe voyage!
安全航海!



高精度风速(0.1m/s)风向仪(1°)
High Resolution Wind Speed(0.1m/s)
& Direction(1°) Anemometer



抗高低温、防潮机械设计、防盐雾
Temperature Resistant & Moisture Proof
Mechanic Design & Salt Proof



七英寸高亮度LCD显示
7inch High Brightness LCD Display



数字与模拟双显示
Digital & Analog Display



AM706

风速风向仪
Marine Anemometer

www.sounder.com.cn

NINGLU

宁禄科技

Item	Specification	参数名	参数指标
Display	7" TFT/480X234 pixels	液晶类型	7" TFT/480X234 像素
Brightness Adjustment	9 Levels Adjustable	亮度调节	九级可调
Data Output	NMEA0183 Wind Speed and Direction	数据输出	NMEA0183风速和风向输出
NMEA Port	RS422 Output 2pin NMEA A/B	NMEA0183接口	RS422 二芯线 NMEA A/B
Direction Accuracy	±1°	风向精度	±1°
Wind Range	0-359°	风向范围	0-359°
Speed Accuracy	0.1m/s	风速精度	0.1m/s
Speed Range	0-60m/s	风速量程	0-60m/s
Startup Wind Speed	≤1.2m/s	最小启动风速	小于等于1.2m/s
Power Supply	24V DC (20-32V) 5W	电源及功耗	24V DC (20-32V) 5W
Operating Temperature	-15 to +55 degree C, We suggest to be 0 to +40 degree C	工作温度	-15至+55°C, 建议0至+40°C
Storage Temperature	-20 to +70 degree C	存贮温度	-20至+70°C
Humidity	10-90% relative, no condensation	湿度	相对湿度10-90%, 非凝结
Protection	IP23	防护等级	IP23
Sensor		传感器	
Operating Temperature	-15 to +85 degree C	工作温度	-15至+85°C
Storage Temperature	-20 to +85 degree C	存贮温度	-20至+85°C
Protection	IP56	防护等级	IP56

安装尺寸
(Installation Dimensions) 单位 (unit) : mm

