

## DET NORSKE VERITAS

## PRODUCT CERTIFICATE

-100mm ay be used in conjunction with installation of	
ion for Echo Sounder, Sonar or Log 3-60-SA, SB-100-LAX_, DB100-SB, -100mm ay be used in conjunction with installation of	
ion for Echo Sounder, Sonar or Log 3-60-SA, SB-100-LAX_, DB100-SB, -100mm ay be used in conjunction with installation of	
ion for Echo Sounder, Sonar or Log 3-60-SA, SB-100-LAX_, DB100-SB, -100mm ay be used in conjunction with installation of	
ion for Echo Sounder, Sonar or Log 3-60-SA, SB-100-LAX_, DB100-SB, -100mm ay be used in conjunction with installation of	
ion for Echo Sounder, Sonar or Log 3-60-SA, SB-100-LAX_, DB100-SB, -100mm ay be used in conjunction with installation of	
3-60-SA, SB-100-LAX_, DB100-SB, -100mm ay be used in conjunction with installation of	
3-60-SA, SB-100-LAX_, DB100-SB, -100mm ay be used in conjunction with installation of	
3-60-SA, SB-100-LAX_, DB100-SB, -100mm ay be used in conjunction with installation of	
3-60-SA, SB-100-LAX_, DB100-SB, -100mm ay be used in conjunction with installation of	
3-60-SA, SB-100-LAX_, DB100-SB, -100mm ay be used in conjunction with installation of	
-100mm ay be used in conjunction with installation of	
-60-SA, DB-60-SA, SB-100-LAX_, DB100-SB, ISJB/ETNSLB-100mm gate valve may be used in conjunction with installation of ed log or echo sounder 65 equirements of:	
Naval 🛛 Offshore	
/alve	
Certificate is only valid when signed by a DNV yor.	
For Det Norske Veritas AS	
: Høvik	
2011-03-03	

Technical data:

Remarks:

The valve housing has been subjected to a hydrostatic pressure test, and the valve assembly to a seat leakage test to 5 bar. Holding time 5 minutes.

Marking and certificate numbers for the different parts:

Drawings with dates of approval and/or type approval certificate number:  $\ensuremath{\text{DNV}}$  S-6000