

DET NORSKE VERITAS

PRODUCT CERTIFICATE

A Safty Ab 131 05 Nacka Sverige
n for Echo Sounder, Sonar or Log 50-SA, SB-100-SBX_, DB100-SB, 00mm be used in conjunction with installation of sounder
n for Echo Sounder, Sonar or Log 50-SA, SB-100-SBX_, DB100-SB, 00mm be used in conjunction with installation of sounder
n for Echo Sounder, Sonar or Log 50-SA, SB-100-SB_X_, DB100-SB, 00mm be used in conjunction with installation of sounder
n for Echo Sounder, Sonar or Log 50-SA, SB-100-SB_X_, DB100-SB, 00mm be used in conjunction with installation of sounder
n for Echo Sounder, Sonar or Log 50-SA, SB-100-SB_X_, DB100-SB, 00mm be used in conjunction with installation of sounder
io-SA, SB-100-SB_X_, DB100-SB, 00mm be used in conjunction with installation of counder
io-SA, SB-100-SB_X_, DB100-SB, 00mm be used in conjunction with installation of counder
io-SA, SB-100-SB_X_, DB100-SB, 00mm be used in conjunction with installation of counder
io-SA, SB-100-SB_X_, DB100-SB, 00mm be used in conjunction with installation of counder
io-SA, SB-100-SB_X_, DB100-SB, 00mm be used in conjunction with installation of counder
00mm be used in conjunction with installation of counder
sounder
🗌 Naval 🛛 Offshore
🗌 Naval 🛛 Offshore
□ Naval
lve
rtificate is only valid when signed by a DNV r.
For Det Norske Veritas AS
løvik
011-05-11
Thomas R. Jacobsen
Surveyor
H

Technical data:

Remarks:

The valve housing has been subjected to a hydrostatic pressure test, and the valve assembly to a seat leakage test to 5 bar. Holding time 5 minutes.

Marking and certificate numbers for the different parts:

Drawings with dates of approval and/or type approval certificate number: $\ensuremath{\text{DNV}}$ S-6000